


DESCRIPTION	SPECIFICATIONS	<div>  <div> <div>Style</div> <div>Scallop Premier</div> </div> </div>	
Gate Width	6', 8', 10', 12', 14', 16', or Special		
Gate Swing	Single, or Double Swing	<div> <div> <div>Ironworks Mfg & Supply</div> <div>300 W. South Street</div> <div>Jackson, MS 39203</div> <div>Phone: 601-352-3722</div> <div>Fax: 601-352-3730</div> <div>www.ironworksmfg.com</div> </div> <div> <div>Mailing Address:</div> <div>P.O. Box 22704</div> <div>Jackson, MS 39225</div> </div> </div>	
Vertical Pickets	5/8" and 3/4" Square Steel Tube 18 Gauge Thickness		
Top Horizontal Rail	1-1/4" Square Steel Tube 14 Gauge Thickness		
Bottom Horizontal Rail	2" Square Steel Tube 14 Gauge Thickness		
Vertical Frame	2" Square Steel Tube 14 Gauge Jam Side, and 11 Gauge Hinge Side		
(2) Post	4" Square Steel Tube 3/16" Wall Thickness		
(2) Post Cap	4" Cast Iron Newel Pyramid, or Newel Post Ball Cap		
Hinges	5" Square, or 7" Square Hinge (2) Per Gate Leaf		
Lock	Cane Bolt with Lockable Hasp, None		
Finial	Die Cast Zinc, Aluminum, Press Point, or Polymer Available		
Size Specifications	Installed Height 4, 5, 6, and 8		